



IPD-HUB 2 PRODUCT SPECIFICATIONS

Description	Powered Dante, 2-channel DSP amplifier
Input Power	PoE, PoE+, 40W PoE, 24V PS
Mounting	Screw-In Base
Inputs	2 x RJ-45, 1 Dante, 1 Axiom
Outputs Connector	2-Channel Phoenix
Speakers	2 x 8 Ω or 4 x 16 Ω speakers
Output Power w/ 40 W PoE	12W / Ch
Height	44.45 mm 1.75"
Width	203.2 mm 8"
Depth	153.4 mm 6"
Weight	3.5 kg 7.71 lbs
Certifications	CE, UL60065, ETL-c/US, UL2043

Description

The IPD-Hub 2 DSP amplifier gives designers and installers an IP-based alternative to traditional 70V/100V distributed audio systems in small to mid-size applications. The IPD-Hub 2 utilizes a Dante infrastructure for flexible audio distribution. The amp is complete with local and Dante inputs and local and network control to address requirements for commercial audio connectivity in numerous applications, such as small to medium size retail, bar, restaurants, hospitality, spas, education facilities, and more.

Features

- Feature rich IP-based, Dante™ connected option for traditional 70V/100V distributed audio systems in small to mid-size applications.
- AES67 Compatible
- Configurable priority paging inputs provided.
- Remote volume control and selection between two sources is supported on the single IPD-Hub 2 with the SoundTube RVC-1.
- Integrated DSP provides input mixing and equalization to optimize the performance of any ceiling or in-wall speaker.
- Software setup through STNet Control Center.
- Included Accessory:
AC-HUB2-CBL-RDL RDL Adapter Cable

SoundTube®

13720 W. 109th St.
Lenexa, KS 66215
Phone: 913.663.5600
Fax: 913.663.3200
Toll Free: 855.663.5600
www.soundtube.com

All SoundTube speakers come with a 5-year limited warranty and 3-year warranty on all electronics.